



Targa PC Card Data Transfer Units Panel Mount or Internal Mount



Overview

Targa's PC Card Data Transfer Units (DTU) provide a compact self-contained system to store and retrieve data from industry standard PCMCIA/ATA cards and have been qualified to meet the most demanding MIL-STD-810 and RTCA DO-160 environments.

- **PC Cards (ATA) capacities: up to 32 GB**
- Small, lightweight, rugged construction providing reliable data storage
- Locking access door with door open detect & PC Card shutdown
- Interfaces: SCSI-2; 8 bit single ended
 Serial RS422/485 and RS232
 USB
 Ethernet
- Input Power +28 V_{dc}, with 20 msec holdup or +5 V_{dc}
- Mounting Panel Mount (DZUS) per MS25212C at K=4
 Internal Mount – 3 ½" disk form factor



Internal Mount



Panel Mount

Model Numbers

Interface			Options			Unit Mounting
SCSI	Serial RS-422/485 RS-232	USB	Power		LED Indicators	
			+24 V _{dc}	+5 V _{dc}		
DR30-10-2	DR30-20-2	DR30-40-2	•	-	-	Panel Mount
DR30-11-2	DR30-21-2	DR30-41-2	-	•	-	
DR32-10-2	DR32-20-2	DR32-40-2	•	-	•	
DR32-11-2	DR32-21-2	DR32-41-2	-	•	•	
HS30-10-2	-	HS30-40-2	-	•	-	Internal Mount
HS32-10-2	-	HS32-40-2	-	•	•	
DR39-10-0	-	DR39-40-0	110 – 220 V _{ac}		•	Desktop



Desktop Unit



communications

Targa Systems Division



communications

Targa Systems Division

Targa's Solid State Storage Solutions are available in a wide range of form factors and interfaces.

- VME
SCSI, ATA, I/O
6U, single slot
- CPCI
USB, SCSI
6U & 3U
- PC Card DTU's
Serial, SCSI;
MIL-STD1553,
Ethernet, USB
- USB Flash Disks
3.5"
- Removable Disk Systems
3.5" and 2.5"

Website: www.targasystems.com

Marketing Offices:

Charlotte, NC, USA

Phone: 704-708-4720

Email: sales@targasystems.com

Headquarters:

Ottawa, Ontario, Canada

Phone: 613-727-9876

Email: sales@targasystems.com

Targa PC Card DTU Specifications

	SCSI	Serial	MIL-STD-1553
Bus Speed	5 MB/sec	9600 – 230 KBaud	1 MBaud
Data Reads	> 850 KB/sec	Protocol Dependent	Protocol Dependent
Data Writes	> 750 KB/sec	Protocol Dependent	Protocol Dependent
Panel Mount Units DR3x-yy-2			
Input Power +28Vdc	RTCA-D0-160 Cat Z 4w max	RTCA-D0-160 Cat Z 4w max	RTCA-D0-160 Cat Z 6w max
MTBF (217F AIC)	35,000 hours	33,000 hours	30,000 hours
Physical	Form factor Per MS25221C K=4 Unit case 1.4"H x 5"W x 6.5"D Front Panel 1.5"H x 5.75"W		
Weight	825 g		
Internal Mount Units HS3x-yy-2			
Input Power	+5 V _{dc} 4w max	+5 V _{dc} 4w max	+5 V _{dc} 6w max
MTBF (217F AIC)	60,000 hours	58,000 hours	55,000 hours
Physical	1.4"H x 4.25"W x 5.5"D		
Weight	525 g		
Environmental			
Temperature	Operating -40°C to +75°C Storage -55°C to +85°C	MIL-STD-810E, Method 501.3 MIL-STD-810E, Method 502.3	
Altitude	50 000 ft	MIL-STD-810E, Method 500.3	
Humidity	10-100% Condensing	RTCA/DO-160D, Sec. 6, Cat. B	
Shock	Operating 40g, 11msec, ½sine	RTCA/DO-160D, Sec. 7 (Modified) & MIL-STD-810E, Method 516.4	
Vibration	PSD 0.04 g ² /Hz, 5 - 2000 Hz PSD 0.02 g ² /Hz, 10 – 300 Hz 0.002 g ² /Hz, 300 - 2000Hz & Injected sine waves @ F2 & F3,	MIL-STD-810E, Method 514.4, Cat10 RTCA/DO-160D, Sec. 8 (Modified)	
Explosive Atm	RTCA DO/160D, Sec. 9, Cat. E		
Waterproofness	RTCA DO/160D, Sec. 10, Cat. W		
Sand & Dust	RTCA DO/160D, Sec. 12, Cat. D		
Fungus	RTCA DO/160D, Sec.13, Cat. F		
Salt Spray	RTCA/DO-160D, Sec. 14, Cat. S		
EMI	MIL-STD-461/462 RTCA/DO-160C	CE01, CE03, CE07, CS01, CS02, CS06, RE01, RE02, RS01, RS02, RS03 Sec. 15, Cat A; Sec. 17, Cat. A; Sec. 18, Cat. B Sec. 19, Cat. Z; Sec. 20, Cat. Y; Sec. 21, Cat Z	